



The **BioCycle-ENR Nitrification (NIT)** process configuration is a solution that is designed for facilities required to meet effluent ammonia limits by managing the oxygen supply under varying loading conditions throughout the life of the treatment facility. Utilizing the FlexZone™ Adaptive Process Volume System, the NIT process transitions excess aeration volume to simultaneous nitrification denitrification (SNDN) operation. This low dissolved oxygen (DO) environment offers alkalinity recovery through denitrification, efficient carbon management, and unrivaled energy savings.



Many plants aren't able to take trains off-line when operating below design conditions. These plants **struggle with excess aerobic volumes**, even with effective DO control strategies in place.

Excess aerobic volumes lead to mixing limited conditions, resulting in high DO concentrations, depleted alkalinity, and excess energy consumption.



The FlexZone system enables aerobic volumes to expand and contract to match changing influent conditions while SNDN operation recovers alkalinity and saves energy.


SyncroMix, the unique combination of BioMix integrated with fine bubble diffused aeration, prevents mixing limited overaerated conditions by providing unlimited turn-down through independent control of aeration and mixing.

The vertical mixing regime of BioMix Compressed Gas Mixing maintains the integrity of low DO and aerobic environments without the need for physical baffled zones.

REDUCING ENERGY CONSUMPTION

According to Water Environment Research Foundation's Roadmap to Net Zero Energy, the three largest opportunities for energy savings at wastewater treatment plants are optimization of the aeration system, addition of an anoxic zone, and flexible sequencing of aeration basins. Utilizing low energy treatment options allows plants to get closer to energy neutrality. EnviroMix's BioCycle-ENR with the FlexZone system is perfectly suited to deliver on all three of these opportunities.

- BioCycle-ENR optimizes the aeration system by matching the oxygen delivery to the oxygen demand through smart aeration controls that have unmatched turn down and allow for low DO SyncroMix environments with independent control of aeration and mixing.
- Reducing required oxygen delivery by manipulating the reactor environment to create anoxic conditions recovers alkalinity and reduces carbon loading through denitrification kinetics.
- The FlexZone system takes sequencing to the next level without compromising mixing by dynamically transitioning excess aerobic capacity to energyefficient mixing or low DO volumes.
- * Water Environment Research Foundation. Exploratory Team Report – Energy Management



KEY ADVANTAGES FOR AN NIT CONFIGURATION



Process Optimization

- Capitalizing on the FlexZone system, BioCycle-ENR utilizes the proven NIT activated sludge process to dynamically adapt the aerobic environment to changing temperature and loading conditions.
- Ability to manage DO and carbon with proper balance of low DO and aerobic volumes to achieve nitrification goals throughout the life of the system.



Energy Efficiency

- Provides energy efficient operation by decoupling aeration and mixing.
- Independently meets mixing and oxygen demands with SyncroMix — concurrent operation of BioMix Compressed Gas Mixing and diffused aeration.



Unparalleled Flexibility

- Offers a process configuration tailored to meet current and future nitrification objectives, optimizing energy consumption and treatment performance.
- Facilitates SNDN to recover alkalinity and reduce chemical consumption.



Straightforward Operation

- Provides easy access to equipment outside of the tank.
- Requires minimal maintenance of in-tank equipment.

www.enviro-mix.com

701 East Bay Street, Suite 502 · Charleston, SC 29403 P: 843.573.7510 · F: 843.573.7531 · E: sales@enviro-mix.com Contact sales@enviro-mix.com

TO OPTIMIZE YOUR NIT CONFIGURATION WITH BIOCYCLE-ENR.